

# CommCare Sync Data

You can use a special URL to view what data will be sent to the phone when it syncs with CommCare HQ.

- View restore data for any mobile user in HQ.
  - View all data associated with a user: [http://www.commcarehq.org/a/{my-project-space}/admin\\_restore/?as={user}@{domain}.commcarehq.org&version=2.0](http://www.commcarehq.org/a/{my-project-space}/admin_restore/?as={user}@{domain}.commcarehq.org&version=2.0)
  - App Specific: [http://www.commcarehq.org/a/{my-project-space}/admin\\_restore/{app\\_id}/?as={user}@{domain}.commcarehq.org&version=2.0](http://www.commcarehq.org/a/{my-project-space}/admin_restore/{app_id}/?as={user}@{domain}.commcarehq.org&version=2.0) (assumes current state of the app, not particular build)
  - Build Specific: [http://www.commcarehq.org/a/{my-project-space}/admin\\_restore/{build\\_id}/?as={user}@{domain}.commcarehq.org&version=2.0](http://www.commcarehq.org/a/{my-project-space}/admin_restore/{build_id}/?as={user}@{domain}.commcarehq.org&version=2.0)
- Additional params:
  - since={previous restore id}
    - Incremental response since the previous sync.
  - items=true
    - Include the item number in the response.
  - overwrite\_cache=true
    - Don't return a cached value but rather recompute the response. Deletes the cache, so the next time you sync on the phone, it will use the newly computed result.
  - raw=true
    - Raw restore response without the UI
  - device\_id={device\_id}
    - Fake a restore from a particular device id. WebApps uses a device ID of the form "WebAppsLogin".
  - app\_id={app\_id}
    - Restore using app aware sync. This will only sync down the reports for that particular application.
  - case\_sync={clean\_owners | livequery}
    - Select which case sync algorithm to use with this restore
  - hide\_xml=true
    - Shows only aggregate case counts, without loading associated XML data